



GmbH

Your partner for door,- window, and facade engineering

Handheld screwdriver

rod form WFT - SD 2200

with slide forepart, shaft guide and depth disconnection

& hose package

- 93.023 - 2200 1/min



**easy handling
combinable with feed unit**

Field of application :

- in connection with an automatic screw feeding device MF-2 or MF-3 and hose package
- the unit is equipped with a fastening system for assembling on plane surfaces (e.g. for use on assembling tables)

Application:

- for screwing fastening elements into metal (e.g. plate with drilling screw), PVC, wood or similar material with depth disconnection, if a torque of 4,5 Nm is not exceeded.

Structure :

- handheld screwdriver rod form (Desoutter) SD 2200 AR
- press-on start
- slide forepart and shaft guide
- easy accessible sliding clutch for torque adjustment
- easy accessible setting of depth disconnection
- 4 fixation drillings for assembling on plane surface

Technical data:

- revs/min:	2200 revs/min
- torque:	1,0 Nm – 4,5 Nm
- weight:	1, 100 kg
- screw-bit:	PH2 ; 127 mm long
- screws	countersunk-, drilling- and self-tapping screws
	screw length 15-40 mm
	screw diameter Ø 3,5 – 4,2 mm
	head diameter Ø 6,0 – 8,2 mm

Working posture :

- type with automatic screw feed: any posture
- type with manual feed: vertical (down) to horizontal posture

Options:

- option manual feed „J“ (interrupt of automatic screw feed)
- option screwer jaw-forepart „B“ to avoid damage on the profile (e.g. caused by opening screwer jaws)
- version as WFR – SD 2200 without depth disconnection with press-on start and sliding clutch



GmbH Geräte- und Vorrichtungsbau
Tel.: 035828 / 72255
Fax: 035828 / 70743

Sohländer Str. 2 02894 Reichenbach OL
Internet: <http://www.gevo-gmbh.de>
E-Mail: kontakt@gevo-gmbh.de